

# ➔ BUSINESS SHREDDER IDEAL 4005

## INNOVATIVE HIGH CAPACITY OFFICE SHREDDERS – HIGH PERFORMANCE AND LARGE VOLUME

SPS - (Safety Protection System) package: electronically controlled, transparent safety flap in the feed opening as additional safety element; EASY\_SWITCH – intelligent control element indicating the operational status of the shredder with varying colour codes and back-lit symbols; automatic reverse and power cut-off (avoids paper jams); automatic stop if the shred bag is full; electronic door protection via a magnetic proximity switch; double motor protection; energy saving mode | photo cell controlled automatic start and stop | ECC - Electronic Capacity Control – indication of the used sheet capacity during shredding process | automatic oil injection on the cutting shafts during shredding operation for constantly high shred performance | convenient 405 mm feed opening | high quality paper clip proof<sup>2</sup> cutting shafts from special hardened steel | models IDEAL 4005 and IDEAL 4005-C/C suitable for safe shredding of CDs/DVDs | 5 years guarantee<sup>2</sup> on the cutting shafts | quiet but powerful 1600 Watt single phase motor for continuous operation | sturdy chain drive and dust-proof gear box housing | high-quality wooden cabinet, mobile on castors | plastic bag suspension with pull-out mechanism on wheels for easy removal of the full bag (models M/C and SM/C with shred container) | approx. 225 litres volume for the shreds

Power connection<sup>3</sup>: 230 V / 50 Hz / 1~, Dimensions (H x W x D): 1010 x 640 x 590 mm, Weight: 115 kg



Cutting size	shreds also
6 mm	
4 x 40 mm	
2 x 15 mm	

### ECC CONTROL



ECC – Electronic Capacity Control: for continuous feeding without creating paper jams the used sheet capacity is indicated during the shredding process.

#### ➔ IDEAL 4005

Shred width	6 mm
Sheet capacity <sup>1</sup>	50-55   42-47
Security level	2
Feed opening	405 mm
Motor capacity	1600 Watt

#### ➔ IDEAL 4005-C/C

Particle size	4 x 40 mm
Sheet capacity <sup>1</sup>	40-45   34-39
Security level	3
Feed opening	405 mm
Motor capacity	1600 Watt

#### ➔ IDEAL 4005-C/C

Particle size	2 x 15 mm
Sheet capacity <sup>1</sup>	25-30   21-26
Security level	4
Feed opening	405 mm
Motor capacity	1600 Watt

#### ➔ IDEAL 4005-M/C

Particle size	0.8 x 12 mm
Sheet capacity <sup>1</sup>	15-17   13-15
Security level	5
Feed opening	405 mm
Motor capacity	1600 Watt

#### ➔ IDEAL 4005-SM/C

Particle size	0.8 x 5 mm
Sheet capacity <sup>1</sup>	10-11   8-9
Security level	"Level 6"
Feed opening	405 mm
Motor capacity	1600 Watt

<sup>1</sup> A4 paper, 70 g/m<sup>2</sup> | 80 g/m<sup>2</sup>

<sup>2</sup> 4005-M/C 0.8 x 12 mm and 4005-SM/C 0.8 x 5 mm: Paper clips and staples have to be removed before shredding. Guarantee 1 year.

<sup>3</sup> other voltages available



I.T.E. Listed 802 D